

MOISTURE ENCOUNTER

NON-DESTRUCTIVE MOISTURE DETECTOR FOR WOOD, FELT-ROOFING, DRY WALL PLASTER AND BRICK



- Uses low-frequency electronic signals
- No probes or pins to cause surface damage
- Detects moisture through paint, varnish, wallpaper, tiles or roofing felt.

Order #153-002

The Moisture Encounter detects moisture beneath the surface being tested by measuring the resistance between two low frequency signals transmitted from conductive pads on the base of the instrument. Since the resistance is decreased six fold by the presence of the moisture a clear accurate signal is achieved. The soft conductive electrode pads on the base of the instrument run smoothly over the surface being tested and immediately identify moisture without scratching or drilling the surface. Simply select the appropriate scale, hold the Moisture Encounter to the surface and read directly from the meter.



Technical Data

1. Measuring method: non-destructive signal (impedance).
2. Measurement frequency: 5-25 KHZ depending on range used.
3. Electrodes: co-planer conductive rubber.
4. Dimensions: 150 x 80 x 30 mm (6 x 3.2 x 1.2 inches).
5. Weight: 260 grams (9 ounces) including battery.
6. Battery: 9 volts PP3 or equivalent.

Distributed in Canada by:
QPC Instruments Inc.