

**Acculab** VI-Series Top Loading Balances

**116-VI- 400g,600g,1200g,2400g,4800g,4kg,6kg,10kg**

**116-VIR- 400g,600g,1200g,2400g,4800g,4kg,6kg,10kg**

**\* VIR- RS232 interface capability to a computer or printer.**



A value priced top loading balance with a memory feature that allows for consecutive weighing of multiple samples with totaled results displayed. Easy auto calibration with 200-gram calibration weight included. Multiple weighing modes. At start up, the unit will default to the last mode used allowing one time set up and hassle free operation. Simple to use parts counting program. Sealed keypad with audio function tone. The housing is specially designed to keep spills out of internal mechanism.

**Product Information:**

Product Type: **Acculab**  
 Model: **Please see chart below.**  
 Series: **VI-Series top loading balances**  
 Capacity: **Please see chart below.**  
 Readability: **Please see chart below.**  
 Linearity: **Please see chart below.**  
 Weighing Modes: **g; oz; ct; dwt**  
 Tare Range: **To capacity by subtraction**  
 Calibration: **auto calibration from keypad**  
 Stabilization Time (sec): **3 seconds**  
 Maximum Overload: **150% of capacity**  
 Overload Indication: **"H" reading on LCD**  
 Underload Indication: **"L" reading on LCD**  
 Auto Off: **AC only**  
 Optimum Temperature: **50-86 F (10-30 c)**  
 Optimum Humidity: **less than 80% RH**  
 Display Type: **LCD/.75**  
 Low Battery Indication: **AC only**  
 Power Requirements: **LCD/.75**  
 Weighing Platform Size: **5.5" x 5.7" (141 x 145mm) stainless,**  
 Dimensions (hwxwd): **3.5" x 5.75" x 10.25" (89x146 x260mm)**  
 Warranty: **2 year limited warranty**  
 Other Features:  
**Built in lock-down bracket. Lock down cable (LC-1) is optional. Includes a 200 g calibration weight and AC adapter. Optional V-Case carrying case available. Shipping weight is 4 lbs. and dimensions are 11.5" x 11" x 7".**

	#116-VI-400	VI-600	VI-1200	VI-2400	VI-4800	VI-4kg	VI-6kg	VI-10kg
	#116-VIR-400	VIR-600	VIR-1200	VIR-2400	VIR-4800	VIR-4kg	VIR-6kg	VIR-10kg
Capacity	400g	600g	1200g	2400g	4800g	4000g	6000g	10000g
Readability	0.1g	0.1g	0.1g	0.1g	0.1g	1g	1g	1g
Linearity	+/- 0.1g	+/-0.1g	+/-0.1g	+/-0.1g	+/-0.1g	+/-1g	+/-1g	+/-1g
Cal. Weight	200g	200g	2x200g	2x200g				
<b>Optional</b>			<b>1000g</b>		<b>4kg</b>	<b>2kg</b>	<b>2x2000g</b>	<b>3x2000g</b>

**R-represents---RS-232 interface capability to a computer or printer.**