

Digital Light Meter

MODEL: TES-1335

Features

- Spectral Sensitivity close to CIE photopic Curve.
- Measuring levels Ranging 0 to 400,000 Lux, 0 to 40,000 fc.
- Relative function.
- Cosine Angular corrected.
- Auto-Power-Off function.
- CNS 5119 Class II
- Peak Hold function.
- Accurate and Instant response.
- Data Hold function.
- MAX/MIN function.



#135-**TES-1335**

Specifications

| | |
|--------------------------------|--|
| Display | 3 3/4 digital LCD with bargraph indication |
| Measuring Range | 40, 400, 4000, 40000, 400000 Lux 40, 400, 4000, 40000 fc (1fc = 10.76 Lux) |
| Overrange Display | Highest digit of (1) is displayed |
| Resolution | 0.01 Lux |
| Accuracy | ±3% rdg ±5dgt (Calibrated to standard incandescent lamp, 2856°K) |
| CIE photopic f '1 | < 9% |
| Temperature Characteristics | ±0.1%°C |
| Measuring Rate | Approximately 2.5 time/sec |
| Photosensor | Silicon photodiodes |
| Operating / Storage Conditions | 0°C - 50°C < 80% RH -10°C - 60°C < 70% RH |
| Power Source | 6 pcs AAA size Battery |
| Battery Life (typical) | 200 hours |
| Photosensor Lead Length | 150 cm (approx.) |
| Photosensor Dimensions | 100(L) X 60(W) X 27(H)mm |
| Dimension | 135(L) X 72(W) X 33(H)mm |
| Weight | 250g |
| Accessories | Carrying case, Instruction manual, Battery |
| Optional Accessories | 1311-HC holster case |