

## J-2000, J-4, and J-Lite for Woodworkers

### Woodworker

Cabinetmakers, woodworkers and craftsman know that excessive moisture can cause major problems in their finished product. Delmhorst offers three solutions for any budget to locate moisture before it affects your work. The J-2000 and J-Lite meters incorporate an advanced micro controller circuit, and all three meters offer you superior value and the high degree of accuracy and reliability you have come to expect from Delmhorst. These meters are ideal for any woodworking application.

The models featured below, purchased individually, includes a carrying case and extra #2497/A-100 contact pins.

#202-J-2000

#202-J-4

#202-J-Lite

The standard package includes the moisture meter, carrying case, #26-ES, and extra #496 and #2497/A-100 contact pins.

Or choose from two different packages depending on your needs.

#202-J-2000/PKG includes J-2000 w/deluxe case, 26-ES, (10)496 pins.

#202-J-4/PKG includes J-4 w/deluxe case, 26-ES, (10)496 pins.



### #202-J-2000

#### Features:

- Microcontroller circuit
- Corrects for 48 individual species and temperature (°F and °C)
- Averages up to 100 accumulated readings
- Measures moisture content over the range of 6% to 40%
- Connector for an external electrode
- One-year warranty
- Packed with features, the J-2000 is popular among woodworkers, small shops, and furniture manufacturers



### #202-J-4

#### Features:

- Popular analog readout
- Moisture content range from 6% to 30%
- Connector for an external electrode
- One-year warranty
- A favorite among woodworkers and small shops



### #202-J-Lite

#### Features:

- Microcontroller circuit for increased reliability and accuracy
- 12 bright LEDs — great for reading in direct sun light or dark areas. Gives the most precise readings of any LED meter available today
- Moisture content range from 6% - 30%
- Connector for an external electrode
- Industry only three-year warranty
- The perfect tool for a hobbyist, woodworker and home inspector

## ELECTRODES

All of the J and BD Series moisture meters come with contact pins mounted on top of the meter and a port used to connect any external electrode. The standard contact pins penetrate maximum 5/16" for stock up to 6/4, and can be used to test wood, concrete and gypsum.

For other applications, consider the following external electrodes:



### #202-26-ES 1 1/8" penetration(insulated pins)

The industry standard for lumber and woodworking, this electrode allows you to determine moisture gradients. The contact pins that come with the 26-ES have insulated shanks so that only the tips are exposed. The pins make contact with the wood fiber only at their uncoated tips and provide much more accurate readings of moisture content at various levels of penetration. Knowing that the board is not uniform, you can use the pins to determine the drying pattern. Ideal for the hardwood flooring installer, furniture manufacturer and the serious craftsman, the 26-ES may be purchased as a separate option or included in one of our moisture meter packages, depending on model.



### #202-21-E 3 1/4" penetration(insulated pins)

Features #608 4" insulated pins for use on EIFS, roofing and insulation or any tests where deeper penetration is required. #608/001 pins also offered in 7" lengths. Required for EIFS inspectors; widely used by roofing contractors, the 21-E may be purchased as an option or included in one of our moisture meter packages, depending on model.



**#202-2-E \$99.00 5/16" penetration**

Uses the same contact pins that are mounted on each meter. This electrode is great to use in hard to reach places. Ideal for the home inspector and pest control operator.

We also offer electrodes for specific applications such as veneer, timber and poles.

## CONTACT PINS

**#202-496/24pcs or /100pcs**

Standard on the 26-ES, the #496 contact pins are insulated except at the tips. 2" overall length, 1 1/8" penetration. Used on wood up to 5" thick.

**#202-1849/24pcs or /100pcs**

A shorter version of the #496, the #1849 has 1/2" penetration and is suitable for wood up to 2" thick.

**#202-A-111/24pcs**

An uninsulated contact pin with 1/2" penetration. Used with the 26-E electrode. May be used on wood up to 2" thick.

**#202-608/4pcs**

Standard on the #21-E, the #608 contact pins are insulated except at the tips. 4" overall length, 3 1/4" penetration. Used on roofing, insulation, timber and poles.

**#202-608/001/4pcs**

A 7" version of the #608, the #608/001 has an overall penetration of 6". This pin was specifically designed to meet EIFS testing standards, and can also be used on timbers and poles.

**#202-2497/A-100/24pcs**

Contact pin and retainer with overall penetration of 5/16". Standard on all J- and BD-series meters and the #2-E electrode. Used on wood up to 6/4, concrete and gypsum.