

True RMS Multimeter

MODEL: TES-2620

Features

- 3-3/4 Digital LCD with Bar-graph
- Water-Proof ABS housing
- Auto-power off
- Two year warranty
- Ohms, Diode Audible continuity, Capacitance input, Overload protection to 600 Vrms

Specifications

IEC 1010

1000V CAT III Pollution 2

Voltage (AC/DC)

Range: 400m/4/40/400/750V (AC)/1000V (DC)
Accuracy: DC - 0.5% rdg + 1 dgt
AC - 1.2% rdg + 5 dgts
Resolution: 0.1mV
Overload Protection: DC 1100V & AC 800V

Current (AC/DC)

Range: 4m/40m/400m/20A
Accuracy: DC - 1% rdg + 1 dgt
AC - 1.5% rdg + 5 dgts
Resolution: 1 μ A
Overload Protection: 0.5A/250V
Fuse & Diode (AC/DC)

Continuity Beeper

Operation Resistance -below 40 Ω
Max Open Circuit Voltage: 0.5V
Max Open Circuit Voltage: 3V

Ohms (Resistance)

Range: 400 Ω /4K Ω /40K Ω /400K Ω /4M Ω /40M Ω
Accuracy: 0.75% rdg + 3 dgts
Resolution: 100m Ω
Overload Protection: 600Vrms
(Also for continuity & Diode, ADP)
Max Open Circuit Voltage: 0.5VDC

#135-TES-2620



Frequency (Hz):

Range: 100Hz/1KHz/10KHz/100KHz/500KHz
Accuracy: 0.1% rdg + 2 dgts
Resolution: 0.01Hz
Sensitivity: 100mV/1V/10V
Sampling Rate:
20 times/sec for Bar-graph indication
2 times/sec for digital display
Power Source: 2pcs of "AA" 1.5V Battery
Dimensions, Weight: 184(L) x 82(W) x 42(H)mm,
Approx. 375g
Accessories: Test leads, Spare fuse, Battery,
Instruction manual, Holster case
Optional accessories: Carrying case

Distributed in Canada by:
QPC Instruments Inc.