

Sound Level Calibrator

MODEL: TES-1356

Features

- 94dB and 114dB Sound Calibration at 1KHz
- Accurate and Simple to use
- Fits 1", 1/2" or 1/4" diameter microphone



Specifications:

#135-TES-1356

Output Sound 114dB and 94dB re 20 uPa under

Pressure Levels: reference conditions

Output Frequency: 1000Hz \pm 4%

Reference Conditions: TEMPERATURE - 23°C(73°F)
ATMOSPHERIC PRESSURE - 1013 mbar (760mm of Hg)
RELATIVE HUMIDITY - 65%

Accuracy of Sound Pressure Level: Under stated reference environment conditions \pm 0.5dB

Power: One 9V battery 006P or IEC 6F22 or NEDA 1604

Battery Test: Internal circuitry checks condition of battery continuously.
Calibrator will not operate at all if battery voltage falls below acceptable range.

Battery Life: About 300 hours

Dimensions: 103(L) x 63(W) x 54(H)mm

Weight: Approx. 270g (include batteries)

Operating Temperature: 0~50°C (32°~122°F)

Operating Humidity: 0~90%RH

Kit Includes: 9V battery, carrying case, Instruction manual,
1" h, 1/2" h and 1/4"

Distributed in Canada by:
QPC Instruments Inc.